


The print-out is not subject to the modification service.

Intended for internal and supplier use

EN

Ident. Doc.: L34

① piston rod processing per
STAB-Spec. 10028959, table 1



thread tolerances acc. to DIN ISO 965-3

$\sqrt{Rz\ 25}$ ($\sqrt{Rz\ 100}$ $Ra\ 0.2$ $Rz\ 100$) $+0.2$ -0.2

AIAG CQI-standards acc. to STAB-Spec. 10027692

Environmental protection acc. to STAB-Spec. 10005649

DE:	EN:	ES:	IT:	PR:	FR:	RO:
new	INITIAL RELEASE					
old	-					
Field	-					
Date/Name	08.02.2016 Höfer					
Chg. No.	633592					
Rev.	0					

CAD created document; handwritten changes not permitted	
RELEASE for supplier	
company Zhang Shi	
Dat. 08.02.2016 Schilz A. (date / signature)	

Material:	1.1193 S45C JISG 4051
Edge tolerances acc. to DIN ISO 13715	
Surface finish	DIN EN ISO 1302
Replaces:	
STABILUS	

All dimensions are in mm	Identification of important characteristics
Scale: (Original DIN A3) 2:1	Dimensions without tolerances DIN ISO 2768-mK
We reserve all rights to this document, to any patents or patent registrations related hereto, and to the duplication, retransmission by third parties and misc. use. Any use of this document is not permitted without the written consent of STABILUS.	
PISTON ROD	

Drawn by	Date	Name
08.02.2016 Höfer		
Checked	08.02.2016 Schilz	
Document No.: 10166619		
Material No.: 160395		