


The print-out is not subject to the modification service.

Intended for internal and supplier use


EN

Ident. Doc.: L12


Ⓐ piston rod processing per
STAB-Spec. 10028959, table 1



RELEASE
for supplier
company Zhang Shi
09.06.2015 Schilz A.
(date / signature)



X 5:1



$\sqrt{Rz\ 25}$ ($\sqrt{Rz\ 100}$ $Ra\ \textcircled{A}$ $Rz\ \textcircled{A}$) $\swarrow +0,2$ $\searrow -0,2$

AIAG CQI-standards acc. to STAB-Spec. 10027692

Environmental protection acc. to STAB-Spec. 10005649

DE:	X	EN:	X	ES:	IT:	PR:	FR:	RO:	CAD created document; handwritten changes not permitted
new		INITIAL RELEASE			run area		R1		
old		-			hardness		0,5x45°		
Field		-			F 4		E/2		
Date/Name	13.11.2008	Höfer	26.7.10	Keßelh.	08.06.2015	Hein			
Chg. No.	-		581811		624059				
Rev.	0		1		2				

Material:	1.1193 S45C JISG 4051
Edge tolerances acc. to DIN ISO 13715	
Surface finish	DIN EN ISO 1302
Replaces:	
STABILUS	

All dimensions are in mm	Identification of important characteristics	Drawn by	Date	Name
Scale: (Original DIN A3) 2:1	Dimensions without tolerances DIN ISO 2768 mK	Checked	13.11.2008	Höfer
We reserve all rights to this document, to any patents or patent registrations related hereto, and to the duplication, retransmission by third parties and misc. use. Any use of this document is not permitted without the written consent of STABILUS.			08.06.2015	Klinkner
		Document No.:	10151520	
		Material No.:	023303	