


The print-out is not subject to the modification service.

Intended for internal and supplier use


EN

Ⓐ piston rod processing per STAB-Spec. 10028959, table 1




**RELEASE**  
for supplier  
company Zhang Shi  
16.07.2015 Schilz A.  
(date / signature)

pre-worked:



X 5:1



$\sqrt{Rz\ 25}$  ( $\sqrt{Rz\ 100}$  Ra Ⓐ Rz Ⓐ)  $\swarrow +0,2$   $\searrow -0,2$

AIAG CQI-standards acc. to STAB-Spec. 10027692

Environmental protection acc. to STAB-Spec. 10005649

DE: X	EN: X	ES:	IT:	PR:	FR:	RO:	CAD created document; handwritten changes not permitted
new	INITIAL RELEASE		R1				
old	-		0,5x45°				
Field	-		E/2				
Date/Name	02.09.2013 Donat		15.07.2015 Hein				
Chg. No.	606652		624057				
Rev.	0		1				

Material:	1.1193 S45C JISG 4051
Edge tolerances acc. to DIN ISO 13715	
Surface finish	DIN EN ISO 1302
Replaces:	
<b>STABILUS</b>	

All dimensions are in mm	Identification of important characteristics	Date	Name
Scale: (Original DIN A3) 2:1	Dimensions without tolerances DIN ISO 2768-mK	02.09.2013	Donat
We reserve all rights to this document, to any patents or patent registrations related hereto, and to the duplication, retransmission by third parties and misc. use. Any use of this document is not permitted without the written consent of STABILUS.		Checked	15.07.2015 Klinkner
		Document No.:	10151065
		Material No.:	547086

Date	Name
02.09.2013	Donat
15.07.2015	Klinkner
Document No.:	10151065
Material No.:	547086

Ident. Doc.: L194