


Color: brown/black
 1.) Bond zone: = 12 +10 µm
 2.) Porous zone: 2-8 µm

Surface treatment
 Surface processing of piston rods < 800mm length according to QPQP
 - process Surface hardness ≥ 430 HV 0,1 DIN EN ISO 6507-1
 Corrosion resistance: 144 h NSS DIN EN ISO 9227

Piston rod free from cracks,
 guaranteed by optical individual test or eddy current test

Finished dimension [mm]			roughness depth after final condition	
permissible runout			run area	no run area
X	I1	I	$R_a = 0,06 - 0,1 \mu\text{m}$ $R_z \leq 0,90 \mu\text{m}$	$R_a \leq 0,20 \mu\text{m}$ $R_z \leq 1,5 \mu\text{m}$
0,05	50	>55		
0,10	100	>105		
0,20	150	>155		
0,30	225	>230		

All dimensions are finished dimensions



We reserve all rights to this document, to any patents or patent registrations related hereto, any to the duplication, retransmission by third parties and misc. use. Any use of this document is not permitted without the written consent of HAHN-Gasfedern.		General-tolerance ISO 2768-m	Edge-tolerances DIN 6784	Sc. 2:1	Art.-Nr.:	Wrought mat.:
Date		Name	Material: S 45 C			
Drawn by 16.09.2020		UGneiting	Weight: 0.402 kg			
Checked			Kolbenstange			
Norm			KST Ø 14 St. mit GWZ M10x12			
			Description:			
			KST_-S-00354-E1			1
			Replacement for:			A3
Rev.	Modification	Date	Name	Replaced by:	MOD-Nr.: KST_-S-00354-EM	

