



CONFIDENTIAL!  
Intended for internal use only

EN

Brevet.datum: 25/06/2021 - 7:0

Ident. Doc.:



supp No.	material no.			A	B
	processing and surface treatment acc. to STAB-Spec.: 10006248 Tab. IV (a) version 1	10006248 Tab. X (a) version 1	10028959 Tab. I (b) version 2	overall length	stud length end-fitting side
1		008780	008780	83.5	16
2		948878	948878	350.5	16
3		949834	949834	410.5	16
4		008845	008845	71.5	16
5		008846	008846	77.5	16
6		008847	008847	62.5	16
7		008849	008849	182.5	16
8		008851	008851	85.0	22
9		962501	962501	398.5	16
10		963218	963218	374.5	16
11		652965	652965	74.5	16
12		508855	508855	119.5	16
13		368326	368326	92.5	16
14		963696	963696	344.5	16
15		965369	965369	326.5	16
16		966086	966086	319.5	16



DE: X	EN: X	ES:	IT:	PR:	FR:	RO: X
new	marking groove removed	⊙ = acc. STAB-Spec. 10258370	100% cleanliness of through hole	new format Internal/Supplier		
old	-	⊙ = RHT 0,4 ... 0,7 mm	Permanent additional inspection 014/01	Supplier drawing separately		
Field	-	C 7-8	B/5-6	-		
Date/Name	12.06.2014 Hein	15.05.2019 Donat	08.06.2021 Hein	25.06.2021 Jablonski		
Chg. No.	614235	678703	677895	698589		
Rev.	5	6	7	8		

Ⓛ dim. before grinding at piston rod dia. 8,2±0,1

Ⓜ knurl-profile manuf. with knurl roll DIN 82 - RAA 0,5



100% cleanliness of through hole

√Rz 25 ( √Rz 100 √Rmax5 √Rmax (a) Ra (b) Rz (b) )

sheet 1 of 2

Material: *		All dimensions are in mm		Marking of special characteristics according to STAB-Spec. 10270932		Date	Name
Edge tolerances acc. to DIN ISO 13715		Scale: (Original DIN A3) 2:1		Dimensions without tolerances DIN ISO 2768-mK		24.01.2008	Höfer
Surface finish DIN EN ISO 1302		We reserve all rights to this document, to any patents or patent registrations related hereto, and to the duplication, retransmission by third parties and misc. use. Any use of this document is not permitted without the written consent of STABILUS.		Document No.:		25.06.2021	Klinkner
Replaces:		STABILUS		PISTON ROD		10152217	
						Material No.:	