

Ident. Doc.:

Erstelldatum: 14/9/2021 - 13:40

Intended for internal and supplier use The print-out is not subject to the modification service.

8		7		6		5		4		3		2		1	
supp. No.		material no.		A		F		version 1 (only self-manufacturing)		* material: 010715					
processing and surface treatment acc. to STAB-Spec. 10006248 Tab. XVI optimized		10006248 Tab. X		10028939 Tab. I		overall length without endfitting									
version 1		version 1		version 2		std									
85		492618		492618		132.0		123.5							
86		494530		494530		303.0		294.5							
87		993562		993562		168.0		159.5							
88		154434		154434		213.0		204.5							
89		422832		422832		324.0		315.5							
90		874306		874306		381.0		372.5							
91		937163		937163		255.0		246.5							
92		235223		235223		177.0		168.5							
93		089673		089673		348.0		339.5							
94		109988		109988		492.0		483.5							
95		110944		110944		308.0		299.5							
96		148228		148228		384.0		375.5							
97		149662		149662		414.0		405.5							
98		151813		151813		130.5		122.0							
99		155637		155637		378.0		369.5							
100		156354		156354		162.0		153.5							
101		160895		160895		135.0		126.5							
102		161612		161612		180.0		171.5							
103		163763		163763		293.5		285.0							
pre-worked: (only self-manufacturing)				X 10:1		0,15 -0,15									
R0,5 ±0,2				R0,54 ±0,2											
Ø5,62 +0,06				Ø5,5 ±0,1											
Ø4,5				Ø5,4											
30°				30°											
45°				45°											
1,7 ±0,1				1,55											
R0,5 ±0,2				R0,15 ±0,05											
				Rz 100											
				Ø6,8 +0,05 -0,10											
				Ø5 +0,05 -0,10											
				Rz 100											
				0+3 hardness											
				Ø10 (a)											
				1,55											
				Ø10 (a)											
				1,5 ±0,1											
				Ø10 (a)											
				339.5 (d)											
				(348.0)											
				Rz 100											
				Ø5 -0,020 -0,120											
				Ø9,15 ±0,15											
				R0,15 ±0,05											
				Ø10 (a)											
				1,55											
				Ø10 (a)											
				1,5 ±0,1											
				Ø10 (a)											
				339.5 (d)											
				(348.0)											
				Rz 100											
				Ø5 -0,020 -0,120											
				Ø9,15 ±0,15											
				R0,15 ±0,05											
				Ø10 (a)											
				1,55											
				Ø10 (a)											
				1,5 ±0,1											
				Ø10 (a)											
				339.5 (d)											
				(348.0)											
				Rz 100											
				Ø5 -0,020 -0,120											
				Ø9,15 ±0,15											
				R0,15 ±0,05											
				Ø10 (a)											
				1,55											
				Ø10 (a)											
				1,5 ±0,1											
				Ø10 (a)											
				339.5 (d)											
				(348.0)											
				Rz 100											
				Ø5 -0,020 -0,120											
				Ø9,15 ±0,15											
				R0,15 ±0,05											
				Ø10 (a)											
				1,55											
				Ø10 (a)											
				1,5 ±0,1											
				Ø10 (a)											
				339.5 (d)											
				(348.0)											
				Rz 100											
				Ø5 -0,020 -0,120											
				Ø9,15 ±0,15											
				R0,15 ±0,05											
				Ø10 (a)											
				1,55											
				Ø10 (a)											
				1,5 ±0,1											
				Ø10 (a)											
				339.5 (d)											
				(348.0)											
				Rz 100											
				Ø5 -0,020 -0,120											
				Ø9,15 ±0,15											
				R0,15 ±0,05											
				Ø10 (a)											
				1,55											
				Ø10 (a)											
				1,5 ±0,1											
				Ø10 (a)											
				339.5 (d)											
				(348.0)											
				Rz 100											
				Ø5 -0,020 -0,120											
				Ø9,15 ±0,15											
				R0,15 ±0,05											
				Ø10 (a)											
				1,55											
				Ø10 (a)											
				1,5 ±0,1											
				Ø10 (a)											
				339.5 (d)											
				(348.0)											
				Rz 100											
				Ø5 -0,020 -0,120											
				Ø9,15 ±0,15											
				R0,15 ±0,05											
				Ø10 (a)											
				1,55											
				Ø10 (a)											
				1,5 ±0,1											
				Ø10 (a)											
				339.5 (d)											
				(348.0)											
				Rz 100											
				Ø5 -0,020 -0,120											
				Ø9,15 ±0,15											
				R0,15 ±0,05											
				Ø10 (a)											
				1,55											
				Ø10 (a)											
				1,5 ±0,1											
				Ø10 (a)											
				339.5 (d)											
				(348.0)											
				Rz 100											
				Ø5 -0,020 -0,120											
				Ø9,15 ±0,15											
				R0,15 ±0,05											
				Ø10 (a)											
				1,55											
				Ø10 (a)											
				1,5 ±0,1											
				Ø10 (a)											
				339.5 (d)											
				(348.0)											
				Rz 100											
				Ø5 -0,020 -0,120											
				Ø9,15 ±0,15											
				R0,15 ±0,05											
				Ø10 (a)											
				1,55											
				Ø10 (a)											
				1,5 ±0,1											
				Ø10 (a)											
				339.5 (d)											
				(348.0)											
				Rz 100											
				Ø5 -0,020 -0,120											
				Ø9,15 ±0,15											
				R0,15 ±0,05											
				Ø10 (a)											
				1,55											