

8	7	6	5	4	3	2	1
material no.			version 1 (only self-manufacturing) * material: 010731				
processing and surface treatment acc. to STAB-Spec. 10006248 Tab. XVI			Nislide (a)				
(a) version 1			(b) version 2				
No.	A	E					
	overall length	length without endfitting stud					
1	956036	252.0	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> </div> <div style="text-align: center;"> </div> </div> <p style="text-align: center;">approved lengths: 50-600 mm</p> <p style="text-align: center;">Environmental protection acc. to STAB-Spec. 10005649</p> <p style="text-align: center;">Marking of special characteristics according to STAB-Spec. 10270932</p> <p style="text-align: center;">Dimensions without tolerances DIN ISO 2768-mK</p> <p style="text-align: center;">We reserve all rights to this document, to any patents or patent registrations related hereto, and to the duplication, reproduction, distribution and use of this document is not permitted without the written consent of STABILUS.</p>				
2	956275	255.0					
3	886968	300.0					
4	490468	111.0					
5	111416	192.0					
6	674504	194.0					
7	164957	243.0					
8	907530	202.0					
9	072465	264.0					
10	077723	336.0					
11	078918	266.0					
12	091824	265.0					
13	096604	137.0					
14	097082	148.5					
15	101145	147.0					
16	110466	154.0					
17	111900	165.0					
18	113095	139.0					
19	121938	90.0					
pre-worked: (only self-manufacturing)							
material: 1.1193 S45C JISG 4051			nitrided run area				
(c) before grinding: Hardness depth and hardness test acc. to STAB-Spec. 10258370			tolerances: $\pm 0,2$ after turning $\pm 0,3$ after straightening $\pm 0,3$ after nisliding				
(d) alternative			Ra (b) Rz (b) Rmax (a) Rz (b) Rz (b) $\pm 0,2$				

sheet 1
of 5

STABILUS

PISTON ROD

Material: *
 Edge tolerance acc. to DIN ISO 13715
 Surface finish DIN EN ISO 1302
 Replaces:

08.04.2021 HeIn
 696948
 3

08.04.2021 HeIn
 696948
 3

08.04.2021 HeIn
 696948
 3

08.04.2021 HeIn
 696948
 3

08.04.2021 HeIn
 696948
 3