

The print-out is not subject to the modification service.


Intended for internal and supplier use

EN

Ident. Doc.:


supp No.	material no.			A	B	E
	processing and surface treatment acc. to STAB-Spec. 10006248 Tab. XVI optimized version 1	10006248 Tab. X version 1	10028959 Tab. I version 2	overall length	thread length	length without end-fitting stud
60	041865	041865	041865	234.0	7	227.0
61	102579	102579	102579	75.0	7	68.0
62	190292	190292	190292	255.0	7	248.0
63	259363	259363	259363	147.0	7	140.0
64	278722	278722	278722	89.0	7	82.0
65	560264	560264	560264	163.0	7	156.0
66	655625	655625	655625	84.0	7	77.0
67	155878	155878	155878	117.0	7	110.0
68	163526	163526	163526	267.0	7	260.0
<b>69</b>	<b>209175</b>	<b>209175</b>	<b>209175</b>	<b>156.0</b>	<b>7</b>	<b>149.0</b>
70	336562	336562	336562	288.0	7	281.0
71	342537	342537	342537	99.0	7	92.0
72	345405	345405	345405	174.5	7	167.5
73	349707	349707	349707	342.0	7	335.0
74	350185	350185	350185	118.5	7	111.5
75	351141	351141	351141	90.0	7	83.0
76	354965	354965	354965	204.0	7	197.0
77	357116	357116	357116	252.0	7	245.0
78	366915	366915	366915	247.0	7	240.0
79	373129	373129	373129	251.0	7	244.0
80	374085	374085	374085	121.5	7	114.5
81	384601	384601	384601	312.0	7	305.0
82	386035	386035	386035	216.0	7	209.0
83	436942	436942	436942	327.0	7	320.0
84	439571	439571	439571	107.0	7	100.0
85	456301	456301	456301	303.0	7	296.0
86	473270	473270	473270	309.0	7	302.0
87	477333	477333	477333	72.0	7	65.0
88	480201	480201	480201	315.0	7	308.0

version 1 (only self-manufacturing) \* material: 010731



(c) before grinding: Hardness depth and hardness test acc. to STAB-Spec. 10258370  
 (d) tolerances:  $\pm 0.2$  after turning  
 $\pm 0.3$  after straightening  
 $\pm 0.3$  after nisliding  
 (e) threaded stud rough-turned dim.  $\phi 5,29_{-0,06}$   
 thread roll tolerance 6e  
 thread tolerances acc. to DIN ISO 965-3

version 2 (only external production) \* material: 1.1193 S45C JISG 4051



thread tolerances acc. to DIN ISO 965-3 approved lengths: 50-600 mm

$\sqrt{Rz 25}$  ( $\sqrt{Rz 100}$   $\sqrt{Rmax (a)}$   $Ra (b)$   $Rz (b)$ )  $\pm 0,2$   $\pm 0,2$

sheet 3  
of 4

AIAG CQI-standards acc. to STAB-Spec. 10027692				Environmental protection acc. to STAB-Spec. 10005649			
DE: X	EN: X	ES:	IT:	PR:	FR:	RO: X	CAD created document handwritten changes not permitted
new	no technical change, no new first sample required			ø8 b no technical change, no new first sample required			Material: *
old	Tab XVI			ø8 a			All dimensions are in mm
Field	F 7			C/3			Marking of special characteristics according to STAB-Spec. 10270932
Date/Name	14.09.2021 Donat			11.11.2021 Hein			Scale: (Original DIN A3) 2:1
Chg. No.	700848			703194			Dimensions without tolerances DIN ISO 2768-mK
Rev.	9			9			We reserve all rights to this document, to any patents or patent registrations related hereto, and to the duplication, retransmission by third parties and misc. use. Any use of this document is not permitted without the written consent of STABILUS.
				<b>STABILUS</b>		PISTON ROD	
						Date: 14.01.2008 Name: Höfer Drawn by: 11.11.2021 Checked: Klinkner Document No.: 10151863 Material No.:	