

The print-out is not subject to the modification service.

Intended for internal and supplier use

Ident. Doc.: SN 53.11*140/32mm 11/2/2022 - 19/5/21

		8		7		6		5				
F	supp No.	material no.					A	B	C	D	E	F
		surface treatment processing acc. to STAB-Spec. 10006248				overall length	stud length piston side	stud length end-fitting side	stud ø piston side	length without end-fitting stud	version	
		table IV Nislide black	table V Nislide light	table VIII Nislide black	table X Nislide "G"							KOST without surface treatment
		for STUS / STMX table IV acc. STAB-Spec. 10210309				only for STUS / STMX						
E	56	471542			471542		225.0	10.5	25	5	200.0	1
	58	531707			531707		306.0	10.5	12	5	294.0	1
	60	0774DM			0774DM		135.0	12.5	16	8	119.0	3
	61	537888			537888		174.0	10.5	10	5	164.0	1
	62	1049DT			1049DT		309.0	12.5	12	8	297.0	3
C	63	544205			544205		270.0	10.5	12	5	258.0	1
	64	546984			546984		210.0	10.5	12	5	198.0	1
	65	556068			556068		156.0	10.5	12	5	144.0	1
	66	556076			556076		258.0	10.5	12	5	246.0	1
	67	556084			556084		357.0	10.5	12	5	345.0	1
B	68	556092			556092		408.0	10.5	12	5	396.0	1
	69	556106		2734QW	556106		456.0	10.5	12	5	444.0	1
	70	563129			563129		204.0	10.5	10	5	194.0	1
	71	563137			563137		252.0	10.5	10	5	242.0	1
	72	563145			563145		303.0	10.5	10	5	293.0	1
A	73	563153			563153		355.0	10.5	10	5	345.0	1
	74	563161			563161		150.0	12.5	10	8	140.0	3
	75	577871			577871		204.0	10.5	12	5	192.0	1
	76	4165YU		4834KX	4165YU		354.0	10.5	12	5	342.0	1
	77	614440			614440		102.0	10.5	10	5	92.0	1
B	79	632538			632538		135.0	10.5	10	5	125.0	1
	81	683833			683833		147.0	10.5	12	5	135.0	1
	82	694134			694134		159.0	10.5	12	5	147.0	1
	86	8778EF			8778EF		648.0	10.5	12	5	636.0	1
	88	9944EV		2744QQ	9944EV		351.0	10.5	8	5	343.0	1
A	90	8372FF			8372FF		180.0	10.5	12	5	168.0	1

AIAG CQI-standards acc. to STAB-Spec. 1002#692

DE: X	EN: X	ES: X	IT:	PR:	FR:	RO: X	CAD created document handwritten changes not permitted				
new	0,5x45° alternative R1	R1 alternative 0,5x45°	Supplier / KOST w/o surface	rom. version created	© = acc. STAB-Spec. 10258370						
old	0,5x45°	0,5x45° alternative R1	internal / -	-	© = RHT 0,4 0,7 mm						
Field	E1	E/1	-	-	C 3-4						
Date/Name	26.5.08 KeDelh.	11.02.2009 Hein	19.05.2014 Donat	20.04.2016 Jablonski	08.05.2019 Jablonski						
Chg. No.	565532	571068	613650	636361	678351						
Rev.	41	42	43	44	45						

Material:				Environmental protection acc. to STAB-Spec. 10005649			
mat. no.: 010715				Identification of important characteristics			
Edge tolerances acc. to DIN ISO 13715				Dimensions without tolerances			
Surface finish: DIN EN ISO 1302				DIN ISO 2768-mK			
Regulations: Zchn.: dt. Nr. v. 08.04.1999				We reserve all rights to this document, to any patents or patent registrations related hereto, and to the duplication, retransmission by third parties and misc. use. Any use of this document is not permitted without the written consent of STABILUS.			
STABILUS				PISTON ROD			
				Document No.: 10003846			
				Material No.:			

